



The Crushing Value Experience

Use the Versatile Environmentally Friendly Solution

Powerful Reciprocating Jaw-Type Excavator Bucket with Removable Sides for both Pulverizing and Crushing Construction & Demolition Waste.



CRUSHING VALUE RANGE OF EXCAVATOR BUCKETS

	CV 8	CV 15	CV 20	CV 28
Recom. Excavator Size (Tons)	< 8T	< 15	< 20 T	< 28 T
Weight (Kg)	780	1500	2000	2800
Opening Width (mm)	660	780	990	1220
Opening Height (mm)	500	580	650	700
Capacity (litres)	200	400	600	900
Output Adjustment (mm)	25-100	25-100	25-100	25-125
Average Crushing Force (Kg/sq,mt)	400600	400600	400600	400600
Max. Capacity (Tons/Hr)	18	35	45	56
Removable Sides	2	2	2	2

The Crushing Value Range of High Quality Excavator Attachments are specifically designed to provide the best possible solution to the on site crushing requirements for construction and demolition contractors, at a time where regulation is determining that certain planned redevelopment is conditional that construction and demolition waste is recycled on location.

***Invest in Technology -
Arrange a Demonstration Today***

www.crushingvalue.com



Crushing on Site

Features:

- Heavy Duty 2 in 1 Crushing and Pulverizing Capabilities.
- Vibration Free, Operator Friendly Functionality.
- Quick and Easy attachment to excavator auxiliary hammer circuit.
- Easily replaceable Carbide Tipped Picks and Hardox Crushing Jaws
- Removable bucket sides gives greater versatility & maximum ROI

www.crushingvalue.com



Easily crushes the larger rubble slabs.



High throat opening with open sides.



Powerful Crushing, No Vibration.

Advantages:

- **More Flexibility**
- **Better Machine Utilization**
- **No Harmful Vibration**
- **Light But Very Sturdy**
- **Quick Attachment**
- **Easy to Use**
- **Reduced Recycling Costs**
- **Obvious Benefits to our Environment.**



MANUFACTURED BY:

Value Tech Ltd.
Dromalour Ind. Park,
Kanturk, Co. Cork.
Ireland.

Tel: 00353 29 51000
Fax: 00353 29 51510
E-mail: info@valuetech.ie
www.valuetech.ie

DISTRIBUTED BY: