



The original for the professionals



AGRO-CENTER
Ihre erste Wahl. *Fliegl*

Mix Master
- versatile capacity ...

Technical data
Mix Master

Versions		200 E	300 E	401 SS	602 SS	802 SS	1002 SS
Max capacity	approx. l	200	300	400	600	800	1000
Weight	approx. kg	240	300	390	540	650	820
Filling diameter	mm	1000	1150	1200	1300	1580	1880
Capacity per hour	approx. m ³	3	4	7	10	12	15
Required power - forklift and wheeled loader	approx. t	-	-	1,5	2	2,5	3,5
Required tractor power	HP	-	-	40	50	80	120
Electro motor	kw	5,5	5,5	5,5	11,0	11,0	18,5
Total height	approx. m	1,35	1,35	1,16	1,16	1,16	1,16

Versions		400 FA	600 FA	800 FA	1000 FA	600 Favorite	800 Favorite
Max capacity	approx. l	400	600	800	1000	600	800
Weight	approx. kg	500	680	810	1050	520	650
Filling diameter	mm	1100	1250	1500	1800	1300	1580
Capacity per hour	approx. m ³	11	15	18	21	10	12
Required power - forklift and wheeled loader	approx. t	2,0	2,5	3,5	5,0	2,0	2,5
Required tractor power	HP	40	60	90	120	50	90
Electro motor	kw	-	-	-	-	-	-
Total height	approx. m	1,26	1,26	1,16	1,16	1,16	1,16

Some versions can be delivered with:
 • Electric motor • Petrol engine • Diesel engine • Hydraulic motor • Mechanical drive (PTO shaft)



Dimensions, weights and technical data are subject to modifications.
 Illustrations are partly with optional equipment. MM 04-2014-GB



Fliegl Agro-Center GmbH · Maierhof 1 · D-84556 Kastl · Tel: +49 (0)8671/9600-50
 Fax: +49 (0)8671/9600-71 · www.agro-center.de · info@agro-center.de

www.fliegl.com

www.agro-center.de

Mix Master FA – with automatic filling and unloading system ...

The economic all-rounder solves without problems the rational mixing technique. Whether it is for civil and underground engineering or agriculture – the original from Fliegl is a worldwide success. The perfect combination of innovative technique, robust construction and flexible application ensures you more efficiency and a long economic life-time:

- Automatic filling system saves time
- Mixing while driving
- Filing, mixing and unloading – all done in the same operation
- No second tractor is required
- Saving labour increases cost effectiveness
- Adjustable mixing legs



- Automatic filling
- With fork slots in mixer frame
- Capacity from 400 to 1.000 l
- Worldwide in use
- Mix can be discharged at any preferred height

Loading shovel ensures fast filling

- Fast unloading due to discharge chute
- Considerably higher hourly output
- Easy to clean
- Also available with wheel loader mounting bracket

Advantages in all applications:

- Unloading with hydraulic loading bucket (serves at the same time as extended discharge chute)
- With tractor mounting bracket
- Universal application for tractor, loader, fork-lift, telehandlers etc.
- For tractor from 35 hp to 140 hp
- Best view of the loading shovel
- Best centre of gravity – close to the tractor

Mix Master SS – the economic all-rounder ...

- Highest quality due to special materials (fine-grained steel)
- Triple bearing in mixing rotor system
- Capacity from 400 to 1.000 l
- Our experience as a mixer manufacturer ensures a solid construction
- Long lifetime expectancy
- Extra strong mesh grid (mixing rotor system is lockable)
- PTO shaft with shear bolt protection
- Splash guard

The all-rounder

Mixes concrete, mortar, grout, fertiliser, feed, compost, garden waste etc.



Mix Master with electric motor

Capacity 200/300 l E
 Filling diameter 1,15/1,15
 Electric motor: KW 5,5/5,5
 Total height 1,25/1,28
 Satellite rotor system ensures highest mix quality

Ideal for gardeners, tilers, builders, homeowners, farmers



Mix Master with wheels, axle, drawbar and swivel discharge chute



- Mixers can be driven in many ways: PTO drive, hydraulic- or electric drive
- Spring mixing legs
- Wall scraper avoids build up on the side wall
- Greaseable mixing rotor bearing
- Best working performance due to optimum gearbox ratio

Mix Master Favorite

- Capacity from 600 to 800 l
- Rear discharge opening
- Strong mesh grid
- PTO shaft
- 1-stage reduction gearbox, gear transmission 1:8
- Mix Master 600 l
- Filling diameter: 1.300 mm
- Mix Master 800 l
- Filling diameter: 1.580 mm
- Splash guard

High performance gearbox FS 150

- 2-stage reduction gearbox
- Transmission 1:11
- Very powerful
- Drive shaft (diameter: 70 mm)



Electric drive (on request)

- Later conversion to electric drive is possible
- Electric drive from 5,5 KW to 18,5 KW with electric switch and cable
- Driven with PTO shaft



Bagging device



Swivel discharge chute extension