



value tech

Multi-Bucket

Excavate → Break → Crush

Multi-purpose excavator crushing bucket with powerful auto-reverse jaw & removable sides.



Heavy duty construction
Flexible 3 in 1 versatility
Easy attach to hammer line
Minimum noise, dust & vibration
Simple for operator to use
Light and easy to transport
Low maintenance cost
Powerful and productive

- Removable Sides -



Simple to detach for pulverizing long and large slabs or unprepared material



Quick and easy to attach for crushing small and prepared material

The Value Tech Multi-Bucket is an essential attachment for companies involved in on site construction, demolition and soil remediation contracts.



Manufactured by: **Value Tech Ltd.**

Dromalour, Kanturk, Co.Cork, Ireland. Tel: 00353 29 51000. Fax: 00353 29 51510

Email: info@valuetech.ie Web: www.valuetech.ie

value tech

Multi-Bucket



Breaking long precast beams with reinforced steel



Breaking large slabs of demolition waste
(No Breaker Required)



Crushing limestone rock to useable output grain size



125mm to dust



50mm to dust

Options: 24V Electro-Magnet
Steel Cutting Blades

TECHNICAL TABLE

VALUE TECH MULTI-BUCKETS

Model	VB 10	VB 15	VB 20	VB 30
Rec. Excavator Weight (Tons)	6-12	13-17	18-24	25-35
Weight (Kgs)	850	1600	2200	2900
Opening Width (mm)	660	780	990	1220
Opening Height (mm)	500	580	650	750
Capacity (litres)	200	400	500	700
Output Size (mm)	25-100	25-100	30-120	30-120
Av. Crushing Force (t/m ²)	400	400	400	400
Max Hydraulic Flow (l/min)	100	160	200	240
Max Hydraulic Pressure (bar)	220	250	250	250
Max Output Capacity (t/h)	15	25	30	40
Removable Sides	2	2	2	2
Tungsten Tipped Picks	6	12	12	15
Bucket Teeth	5	4	5	5

SPECIAL FEATURES

- Special hydraulic system
- Side cutting bars
- Base cutting bar
- Hardox wear surfaces
- Bolt on hitch system
- Cylinder rod protection
- Hydraulic relief system
- Interchangeable jaws
- No rotary movement



Output rates are for indication purposes only, always dependant on material type & operator ability.

www.valuetech.ie

All dimensions given are for indication purposes only. Value Tech Ltd reserves the right to modify specification without notification.